#### **COIN TIMERS**

# iternet





- Single denominational.
- Double insulated.
- Adjustable time 0 to 999 minutes.
- Can be set from 1 to 9 coins to start the timed period.
- Electronic coin scanning.
- Coin on a string protection.
- Power failure protection.
- 15 amp switch rating.
- 240 Volt or 12 Volt
  Accurately checks coins operated.
- Dimensions: 151mm H x 70mm W x 120mm D.





#### **Ultimate in Technology**

- Multi-denominational. Accepts 5¢, 10¢, 20¢, 50¢, \$1 and \$2 coins.
- Adjustable time for coins inserted.
- Adjustable minimum charge to start timer.
- Coin on a string protection.
- for metal type as well as dimensions.
- Time period dependant on coins inserted.
- In-built time remaining display.
- Double insulated.
- 10 amp switching.
- Dual input voltage 240V and 12V.
- Pre-warning of power disconnection.
- Dual output circuits.
- Accepts various programmes to suit specific applications.
- Dimensions: 151mm H x 70mm W x 135mm D.



#### **MODEL AO**

Includes coin box and housing for any electronic coin timer. These housings are part of a larger range designed to varied applications. suit Details on application.

Dimensions: 300mm H x 75mm W x 180mm D.



#### **PANEL MOUNT PM - 20/22 SERIES**

Through the wall mounting / cash drawer. AO housing with surround.

- Dimensions:350mm H x 125mm W x 180mm D.
- Dimensions for through the wall mounting / cash drawer 300mm H x 75mm W x 180mm D.

#### **COIN TIMERS continued...**

## internet

#### 10 SERIES

Dimensions: 240mm H x 198mm W x 89mm D.

#### COIN COUNTER

A counter can be fitted to record the number of coins inserted.

## TIME REMAINING DISPLAY

Separately mounted display can be added to the CT20F, CT20MF and CT20MD coin timers.

Dimensions: 91mm H x 78mm W.



#### **TOKEN OPERATION**

Equipment can be supplied to operate by a special token. The label on the timer then reads "For operation insert token". Stock tokens can be supplied and special tokens with customers embossing can be produced.



#### CT10MD

### Technology Plus Quality Option

- Multi-denominational. Accepts 10¢, 20¢, \$1 and \$2 into the same coin entry.
- Time period dependant on coins inserted.
- Fully adjustable time.
- Double insulated.
- Can be set from 10¢ to \$10 to start the timed period.
- Electronic coin scanning.
- Coin on a string protection.
- Power failure protection.
- 25 amp switch rating.

#### **Options**

- 45 amp switch rating.
- 3 phase switching rating.
- 240V or 12V operated.
- Pre-warning of power disconnection.
- Dual timing circuits available.
- Time remaining display.
- Accepts various operating programs such as:-
  - \* Coins equals kilowatt hours.
- \* Floodlighting control systems.
- \* Photocopier control.
- \* Water metering. (Refer separate data sheets).



#### CT10F

### Low Cost - quality and features at a basic cost.

- Single denominational.
- Double insulated.
- Adjustable time 0 to 999 minutes.
- Can be set from 1 to 9 coins to start the timed period.
- Electronic coin scanning.
- Coin on a string protection.
- Power failure protection.
- 240V or 12V operated.
- 25 amp switch rating.
- 45 amp switch option.

